

FUJITSU Document Scanner f1-7300NX (with PaperStream IP Net



# Flexible distributed capture made simple

Built-in Wi-Fi, Ethernet, and USB connections give you the freedom to locate your scanner in the most convenient, ergonomic place


## Put your scanner anywhere with PaperStream IP Net

Optimize your office space and place the scanner wherever needed, without the limitation of USB cable. We've added both Wi-Fit and Ethernet connectivity to our popular fi-7160 workgroup scanning platform, so the scanner can now be positioned to improve worker productivity and reduce interruptions.

Standard TWAIN and ISIS software packages work seamlessly. With new PaperStream IP Net, you have all the powerful cleanup and seamless application connectivity of the PaperStream IP driver over

the network. Installation is simple: just select the IP address of the scanner to tie it to your standard data-source. Your software will work the same with no changes! No training needed.

PaperStream Capture integration enables push scanning. Your capture profiles will show up on the scanner's 4.3" color touchscreen. Just drop documents in, press the job button, and PaperStream Capture will scan and save all of your documents to your pre-configured destination.



- tablet-based retail environments
- areas where space is tight
   like small workspaces and cramped desks;
   put it anywhere with Wi-Fi capability





TWAIN and ISIS drivers allow universal compatibility with popular scanning and document manage-



### Work untethered

Now you can place the scanner wherever it's best for you; no need for it to be near your PC. 2.4- and 5-GHz wireless, Ethernet, and USB options let you build your workspace to fit your needs.



### Clear, high-quality scans every time

Cutting-edge PaperStream image processing resides in PaperStream IP Net, optimizing every scan automatically to make it the clearest, most legible scan possible.

PaperStream Capture, included, is simple, front-end capture scanning software and boasts a simple user interface which decreases operator training times. Compatible with TWAIN and ISIS, PaperStream Capture makes document capture easier and faster with single button scanning and release options.

Optional PaperStream Capture Pro adds data extraction and indexing, image import capabilities, and multi-station licensing. Call us or ask your reseller for



- Best-in-class automatic feeding of paper, mixed batches, and plastic cards
- Scans a page per second!
  Fast 60ppm/120ipm keeps up with
  your workload
- Built-in Wi-Fi supports 2.4- and 5-GHz networks for fast through-put no matter where you put it
- 4.3" color touchscreen can be configured to display scanning profiles when used with Paper-Stream Capture and Capture Pro software
- Exit tray slides out of the way to save space when not in use



### Put it anywhere with built-in Wi-Fi or Ethernet

- Make it easy-to-reach
- Unclutter desks
- Optimize your workspace
- Make your office look clean and professional

# FUJITSU Document Scanner **fi-7300NX** (with PaperStream IP Net

Technical	Information
-----------	-------------

lechnical Information		
Scanner Type	ADF (Automatic Document Feeder), Duplex	
Scanning Speed*1 (A4 Portrait) (Color*2/Grayscale*2/Monochrome*1)	Simplex: 60 ppm (200/300 dpi) Duplex: 120 ipm (200/300 dpi)	
Image Sensor Type	Color CCD x 2 (front x 1, back x 1)	
Light Source	White LED Array x 2 (front x 1, back x 1)	
Optical Resolution	600 dpi 50 to 600 dpi (adjustable by 1 dpi increments), 1,200 dpi (driver) <sup>8,5</sup>	
Output Resolution** (Color / Grayscale / Monochrome)		
Output Format	Color: 24-bit, Grayscale: 8-bit, Monochrome: 1-bi	
Background Colors	White / Black (selectable)	
Document Size		
Maximum*6	216 x 355.6 mm (8.5 x 14 in.)	
Minimum**	50.8 x 54 mm (2 x 2.1 in.)	
Long Page Scanning**	5,588 mm (220 in.)	
Paper Weight (Thickness)		
Paper	27 to 413 g/m² (7.2 to 110 lb)*°	
Plastic Card	1.4 mm (0.055 in.) or less*10	
ADF Capacity*****	80 sheets (A4 80 g/m² or Letter 20 lb)	
Multifeed Detection	Overlap detection (Ultrasonic sensor), Length detection	
Paper Protection	Lag detection, Sound detection (iSOP)*16	
Display	4.3 in. TFT color touch screen	
Authentication	Keyboard (on touch screen), NFC	
Interface	USB 3.1 Gen1 / USB 3.0 / USB 2.0 / USB 1.1	
Network Interface	10BASE-T, 100BASE-TX, 1000BASE-T	
Network Protocols	IPv4*15, TCP, UDP, ICMP, DHCP, HTTP/HTTPS, DNS	
Power Requirements	AC 100 to 240 V ±10 %	
Power Consumption***		
Operating	42 W or less	
Power Saving	2.4 W or less	

Environmental Compliance	ENERGY STAR®, RoHS
Dimensions* <sup>17</sup> (Width x Depth x Height)	300 x 202 x 170 mm (11.8 x 7.9 x 6.6 in.)
Weight	4.9 kg (10.8 lb) or less
Supported Operating System	Windows® 10 (32-bit/64-bit), Windows® 8.1 (32-bit/64-bit), Windows® 7 (32-bit/64-bit), Windows Server® 2016 (64-bit), Windows Server® 2012 R2 (64-bit), Windows Server® 2012 R2 (64-bit), Windows Server® 2012 R2 (64-bit), Windows Server® 2012 R3 (24-bit), Windows Server® 2018 R2 (64-bit), Windows Server® 2018 R2 (64-bit), Windows Server® 2018 R2 (64-bit), Windows Server® 2018 R3
Included Software / Drivers	PaperStream IP Driver (TWAIN/TWAIN x64/ISIS), WIA Driver** PaperStream Capture, ScanSnap Manager for It Series**, Software Operation Panel, Network Setup Tool, ABBTY FineReader for ScanSnap****, Scanner Central Admin
Image Processing Functions	Error diffusion, Dither
Included Items	Chuter unit, AC cable, AC adapter, USB cable, Setup DVD-ROM

Carrier Sheets	PA03360-0013	Each package contains 5 carrier sheets

Consumables				
Brake Roller	PA03670-0001	Every 200,000 sheets or one year		
Pick Roller	PA03670-0002	Every 200,000 sheets or one year		
Cleaner F1	PA03950-0352	100 ml bottle for Roller cleaning		
Cleaning Wipe	PA03950-0419	1 pack (24 sheets) for Roller deaning		
Cleaning Paper	CA99501-0012	1 pack (10 sheets) for use with Cleaner E1		

US Warranty

1 Year Advance Exchange included
Extended Advance Exchange and Depot options available



A falsal across posed; are affected for common your deporting on the Pengli of the commend concerns. \*\*J. Indicated posed; are from using PEG compression. \*\*J. Indicated posed; are from the pengli of the commend concerns. \*\*J. Indicated posed; are from using PEG compression. \*\*J. Indicated posed; are from the pengli of the commend concerns. \*\*J. Indicated posed; are from the pengli of the commend concerns. \*\*J. Indicated posed; are from the pengli of the commend concerns. \*\*J. Indicated posed; are from the pengli of the commend concerns. \*\*J. Indicated posed; are from the pengli of the pengli





Operating Environment



Relative Humidity 20 to 80% (non-condensing)



Fujitsu Computer Products of America, Inc. 1250 East Arques Avenue, Sunnyvale, CA 94085 888.425.8228 Sables : 80.66.66 Kebnícal Support us.fujitsu.com/fcpa · info@fcpa.fujitsu.com







... 5 to 35 °C (41 to 95 °F)